

Flexible Couplings

Flexseal

Couplings & Adaptors

226-229

CIVILS

Flexseal

Couplings & Adaptors

EPDM Rubber Standard Couplings

Code	Diameter mm	Length mm	Width mm
SC115	100-115	130	120
SC120	110-121	135	120
SC125	110-125	140	120
SC137	120-137	150	120
SC150	125-150	165	136
SC165	140-165	180	136
SC175	150-175	190	136
SC185	160-185	200	136
SC200	175-200	215	150
SC215	190-215	230	150
SC225	200-225	240	150
SC250	225-250	265	150
SC265	240-265	280	150
SC275	250-275	290	150
SC290	265-290	305	150
SC310	285-310	325	190
SC320	295-320	335	190
SC335	305-335	350	190
SC345	315-345	360	190
SC360	340-360	375	190
SC370	345-370	385	190
SC385	355-385	400	190
SC395	370-395	410	190
SC410	385-410	425	190
SC425	400-425	440	190
SC430	405-430	445	190
SC445	420-445	460	190

Code	Diameter mm	Length mm	Width mm
SC450	425-450	465	190
SC465	435-465	480	190
SC470	445-470	485	190
SC490	465-490	505	190
SC510	480-510	525	190
SC525	495-525	540	190
SC540	510-540	555	190
SC550	520-550	565	190
SC560	530-560	575	190
SC570	545-570	585	190
SC580	555-580	595	190
SC600	570-600	615	190
SC620	590-620	635	190



All products comply with WIS4-41-01 EN295 CE.

Flexseal Large Diameter Couplings

Code	Diameter mm	Width mm
LC600	600-699	190
LC700	700-799	190
LC800	800-899	190
LC900	900-999	190
LC1000	1000-1099	190
LC1100	1100-1199	190
LC1200	1200-1299	190
LC1300	1300-1399	190
LC1400	1400-1499	190
LC1500	1500-1599	190
LC1600	1600-1699	190
LC1700	1700-1799	190
LC1800	1800-1899	190
LC1900	1900-1999	190
LC2000	2000-2099	190



All products comply with EN295 CE.

EPDM Rubber AC Adaptor Couplings

Code	Diameter mm	Length mm	Width mm
AC4000	121-136 / 110-121	150	100
AC6000	180-200 / 160-180	220	150
AC9001	260-285 / 180-205	300	150
AC633*	53-63 / 40-50	80	90
AC894*	75-89 / 53-63	105	90
AC1155	100-115 / 75-90	130	90
AC1201	105-120 / 35-45	135	100
AC1225	110-122 / 48-56	140	100
AC1226	110-122 / 60-68	140	100
AC1221	110-122 / 80-95	140	100
AC5144	110-125 / 100-115	140	100
AC1361	121-136 / 80-95	150	100
AC1362	121-136 / 100-115	150	100
AC1452	130-145 / 110-125	160	100
AC1552	140-155 / 90-105	170	100
AC1602	144-160 / 110-122	175	150
AC1603	144-160 / 121-136	175	150
AC1702	155-170 / 110-125	185	150
AC1703	155-170 / 130-145	185	150
AC1922	170-192 / 110-122	205	150
AC1923	170-192 / 121-136	205	150
AC1924	170-192 / 144-160	205	150
AC2000	180-200 / 130-145	215	150
AC2001	180-200 / 155-170	215	150
AC2100	185-210 / 100-115	225	150
AC2101	185-210 / 160-180	225	150
AC2154	190-215 / 150-165	230	150
AC2254	200-225 / 160-175	240	150
AC2352	210-235 / 110-122	240	150
AC2353	210-235 / 121-136	240	150
AC2354	210-235 / 144-160	240	150
AC2355	210-235 / 170-192	240	150
AC2356	210-235 / 190-215	240	150
AC2654	240-265 / 144-160	280	150

Code	Diameter mm	Length mm	Width mm
AC2655	240-265 / 170-192	280	150
AC2656	240-265 / 190-215	280	150
AC2657	240-265 / 210-235	280	150
AC2754	250-275 / 160-175	290	150
AC2756	250-275 / 200-225	290	150
AC2904	265-290 / 144-160	305	150
AC2907	265-290 / 210-235	305	150
AC2908	265-290 / 235-260	305	150
AC3204	295-320 / 144-160	335	150
AC3205	295-320 / 170-192	335	150
AC3207	295-320 / 210-235	335	150
AC3208	295-320 / 240-265	335	150
AC3209	295-320 / 265-290	335	150
AC3608	335-360 / 240-265	375	165
AC3609	335-360 / 265-290	375	165
AC3600	335-360 / 295-320	375	165
AC3858	360-385 / 240-265	400	165
AC3859	360-385 / 265-290	400	165
AC3850	360-385 / 300-325	400	165
AC4208	395-420 / 240-265	435	165
AC4209	395-420 / 265-290	435	165

EPDM Rubber AC Off-Set Adaptor Couplings

Code	Diameter mm	Length mm	Width mm
AC1603o/s	144-160/121-136	175	150
AC2152o/s	195-215/100-115	230	150
AC2906o/s	265-290/185-210	305	150
AC2956o/s	270-295/185-210	310	150
AC3351o/s	310-335/180-205	350	150

All products comply with EN295 CE.

* These products comply with CE.

All products comply with EN295 CE.



Flexseal

Couplings & Adaptors

EPDM Rubber AR Adaptor Couplings

Code	Diameter mm	Length mm	Width mm
AR1500	160-170 / 170-192	215	100
AR2250	240-250 / 260-285	300	130
AR3000	325-335 / 360-385	400	160

All products comply with EN295 CE.



EPDM Rubber 200mm Gully Seals

Code	Diameter mm
GS200	200
GS210	210



EPDM Rubber 100mm Multibushes

Code	Diameter mm
MB100	100
MB150	150

All products comply with WIS4-41-01 EN295 CE.



Lateral Connection for Structured Walled Pipes

Code	Diameter mm
PA Saddle	300-600
UA Saddle	600-2100

All products are WRc approved.



PA Saddle.



UA Saddle.

Flexible Saddle for Concrete Pipes

Code	To suit main pipe with internal diameter	To suit main pipe with wall thickness	To suit main pipe with lateral pipe diameter
FA150B *	375-1500	50-150	DN150
FA150ST †	250-300	22-51	DN200
FA200B *	450-1500	50-150	DN150

* These products are WRc approved.

† Also suitable for Clay Pipes.



FA150B.

Check out our huge range of Clay Drainage...



Pages 87-114

